Mboxes

"What kind of content is my mbox returning?"

MboxDebug is a utility that can be used on an URL that includes a reference to the mbox.js file.

This utility display information about the user's cookie, the user's Test&Targer/Test&Target1:1/ Recommendations profile, and information about each mbox on the page. MboxDebug can be used to view the response from the Test&target server for each mbox.

append ?mboxDebug=1 or http://demo.testandtarget.omniture.com/demo/store/?mboxDebug=1 &mboxDebug=1 to URL mboxDebug window appears:

Mbox Debug Window (version: 39) mbox.js version Page: http://demo.testandtarget.omniture.com/demo/store/?mboxDebug=1 Referrer: Enabled: true was cookie set? Cookies: 'sc locale=en US; sc locale numbers=en US; sc def dir=sc14; mbox=PC#1270834305656-162685.19#1274395938|session#1271803473717-997850#1271805798 s_dslv=1271711461266; mbox-admin=PC#1270839620958-476351.05#1273013337|session#1271803473722-635402#12718 s_lv=1271803739403; s_vnum=1273432016949%26vn%3D11; mboxNoLogging=demo3#false; SESSdefff196fa2a1f8b893e696d53444c35=8ccdf19ee9d87a855fb16006c39e5a85; cms_site_lang=1; s_cid=1440; imploded_vars=4.58.104.42%7CNow+Defined+by+Test+and+Target%7C; elgCustomerGUID=e43b8e38-d144-4f93-b48b-d25fa5da6bd3; s_iid=28048; omniture_unique=95139699903c80fe28181274b26b045e; s_cc=true; s_p_vis=1; s_sq=esportaldev %3D%2526pid%253Dhttps%25253A//ark.omniture.com/es/tools login_v2.php%2526oid%253Dfunctiononclick%252528event%252529%25257B%252520%252520m s lv s=Less%20than%207%20days; s invisit=true; JSESSIONID=4C26F34DD409382A768F5E59740C96FF; X-Mappingobodhgke=BBFA48AD8BD202FF236AFF4F50EB82D2' · Factory: 'default' o pageld: 1271803937442-467433 visitor's unique ID mboxPC: 1270834305656-162685.19 sessionId: 1271803473717-997850 visitor's sessioin ID mbox name and link 1. 'cssStyleOverides' to view response parameters: 'screenHeight=1200, screenWidth=1920, browserWidth=1152, browserHeight=903, browserTimeOffset=-420, colorDepth=24' http://demo3.tt.omtrdc.net/m2/demo3 /mbox/standard?mboxHost=demo.testandtarget.omniture.com& mboxSession=1271803473717-997850&mboxPC=1270834305656-162685.19& mboxPage=1271803937442-467433&screenHeight=1200&screenWidth=1920& browserWidth=1152&browserHeight=903&browserTimeOffset=-420&colorDepth=24& mboxCount=1&mbox=cssStyleOverides&mboxId=0&mboxTime=1271778737713& mboxURL=http%3A%2F%2Fdemo.testandtarget.omniture.com%2Fdemo%2Fstore %2F%3FmboxDebug%3D1&mboxReferrer=&mboxVersion=39

Modified on Tue Apr 20 2010

2. 'headerLogo'

Page 1

Mboxes

"What kind of content is my mbox returning?"

Click on a linked mbox name to view the response from the mbox servers.

parameters: 'screenHeight=1200, screenWidth=1920, browserWidth=1152,

2. 'hea rameters: 'screenHeight=1200, screenWidth=1920,

There are 3 options for response types: 1) No content returned, default content on the page is then displayed.

```
http://demo3.tt...&mboxVersion=39
mboxFactories.get('default').get('homePageFeaturel',0).setOffer(new mboxOfferDefault()).loaded()
```

-This response occurs when:

- -the mbox is not a display mbox in any campaign this visitor qualifies for. -the mbox is in an active recommendation, but there is no recommendations content to display
- Campaign default content is returned.

```
var mboxCurrent=mboxFactories.get('default').get('headerLogo',0);mboxCurrent.setEv
   mboxDefaultContentOffer = function() {
     this._onLoad = function() {};
   _mboxDefaultContentOffer.prototype.setOnLoad = function(_onLoad) {
     this._onLoad = _onLoad;
    _mboxDefaultContentOffer.prototype.show = function(_mbox) {
     var _defaultDiv = _mbox.getDefaultDiv();
if (_defaultDiv == null) {
       return 0;
     _defaultDiv.onclick = function() {
       // just use _mbox.getName() when everyone is on mboxVersion >= 21
       var _mboxName = _mbox.id ? _mbox.id : _mbox.getName();
var _clickDiv = document.getElementById('mboxClick-' + _mboxName);
       if (_clickDiv != null) {
         _clickDiv.onclick();
       }
     };
     var _result = _mbox.hide();
if (_result == 1) {
       this. onLoad();
     return _result;
   mboxCurrent.setOffer(new _mboxDefaultContentOffer());
   if (mboxCurrent.getFetcher && mboxCurrent.getFetcher().getType() == 'ajax') {
     mboxCurrent.show();
   };document.write('</div>');mboxCurrent.setEventTime('include.end');mboxFactories.q
 -Similarly to above, this triggers the default content on the page to display, but this response is served when the
visitor falls into an experience that has "default content" selected instead of an offer to display. This allows
```

Test&Target or Recommendations to track the behavior of the visitor in the experience. Modified on Tue Apr 20 2010 Page 2

"What kind of content is my mbox returning?"

Mboxes

var mboxCurrent=mboxFactories.get('default').get('homePageHero', 0);mboxCurrent.setEventTime('include.start');document.write('<div

3) Offer content is returned.

style="visibility: hidden; display: none" id="mboxImported-default-homePageHero-0">');document.write('<!-- Offer Id: 38618 --><style> \n .m2OfferDefault {\n font-family: verdana,arial,helvetica,sans-serif;\n fontsize: 10px;\n}\n\n.m2OfferDefault a:link {\n color: #333399;\n}\n \n.m2OfferDefault a:hover {\n color: #6666cc;\n}\n\n.m2ProductImage {\n border: none;\n}\n\n.m2Offer table {\n border: 0;\n margin: 0;\n padding: 2;\n}\n\n align: texttop;\n }\n\n<\/style>\n\n<div class= \n .m2ProductImage {\n "m2Product\">\n \n <a href=\"http:\/\/demo.ttdemo.com\/demo\/store\/products\/product_detail.jsp?productId=3\" class= <img class=\"m2ProductImage\" name=\"Offer Image\" src=</pre> \"m2OfferDefault\">\n \"http:\/\/admin3.testandtarget.omniture.com\/admin\/getimage?id=1179\" \/>\n <\/span>\n<\/div>');document.write('</div>');mboxCurrent.setEventTime ('include.end');mboxFactories.get('default').get('homePageHero',0).loaded(); -Encoded offer content from Test&Target or Recommendations is displayed on the page. -can search for "<!-- Offer id:" in response to see which offer is being displayed.